


Brunel Engineering Services Limited



**MADE IN
BRITAIN**



- Apply silicon Peel & Seal easy close to your eCommerce products
- Retrofit onto your existing transport carrier for in line application
- Increased productivity and machine availability
- Quality silicon release liners through precise adhesive applications, even at high speeds
- Millimeter precise transport and positioning of silicon strip material
- Low cost alternative to double sided adhesive tapes
- Full support from our UK service Team

E Commerce packaging with silicone release liners are particularly popular in today's world. With the BES Peel & Seal applicator, you will be able to apply the silicone release liners to your products.

The Peel and Seal Applicator applies a narrow strip of PS hot melt adhesive using a coating nozzle, to a cardboard flap, usually the packaging lid. Next, a silicone release paper is precisely applied onto the glue via the tape applicator. The silicon paper strip is usually slightly longer than the underlying adhesive application for easier removal.

Unlike an adhesive tape, the amount of adhesive can be adjusted flexibly and simply, depending on the surface and use (corrugated or solid cardboard). This can reduce adhesive consumption and lower costs. Furthermore, the flexible adjustment ensures the correct adhesion for later, secure closure. Settings and format changes are easy and quick via an integrated touch control panel.

*Brunel Engineering Services
Limited*

Linked in **YouTube**

Email: general@brunelengineeringservices.co.uk

Web: www.brunelengineeringservices.co.uk

Tel: 01225 784019

Company Registration No: 7094392

Print Finishing and Packaging Solutions

3 Lancaster Park, Bowerhill, Melksham Wiltshire, SN12 6TT

Brunel Engineering Services Limited





The BES Peel & Seal Tape real size is up to 450mm diameter, typically 18-25mm wide, with a 3" core.

The system can be run at linear speeds of up to 50mtrs/min.

Intended for board envelope sealing, typically using corrugated board.

The Peel and Seal system requires mounting to a transport device. We can provide such a device, or it is likely that the equipment can be retrofitted to your carton-folder-gluer. Our engineers are available to visit and assess your own transport device.



- Application Speed: Up to 50mtrs per minute
- Tape Sizes: Tape guides available from 18– 26mm silicone release liner, optional sizes on request
- Tape Type: Silicone release without adhesive
- Tape Capacity: 450mm diameter roll max, 76mm (3") core
- Substrate: Applies tape on to 300gram card and above, subject to transport guiding
- Minimum applied tape length: 50mm, shorter lengths by experimentation
- Mount Bracket: Multi-adjustable for tracking, squareness, tilt and vertical positioning
- Electrical Supply: 120-230vAC 50/60 Hz 2amp
- Air Supply: 4 bar minimum, less than 10 nl/min
- Pre loop dispenser c/w substantial mounting bracket and ancillaries
- Control:- Via an adhesive pattern controller or host machine PLC, 3-24vdc signal



Brunel Engineering Services
Limited

Print Finishing and Packaging Solutions

Linked in YouTube

Email: general@brunelengineeringservices.co.uk

Web: www.brunelengineeringservices.co.uk

Tel: 01225 784019

Company Registration No: 7094392

3 Lancaster Park, Bowerhill, Melksham Wiltshire, SN12 6TT